

Specification for Quotation Q_____

Seacom – Gooseneck SH36 XT



*Sample picture,
may contain options*

Design:

- Heavy duty steel construction designed to lift and tow roll trailers up to 120 tons payload
- Designed for terminal tractors with hydraulic lift fifth-wheel plates with a lifting capacity of 36 tons
- Lightest weight in the industry due to structure of fine-grained steel
- King pin plate made of Hardox
- Easy hookup to tractors and roll trailers
- Goosenecks can be stowed in park boxes when not in use (optional)
- Safety chains available for added safety (optional)

Finish:

- Gooseneck completely shot blasted to SA 2½ after welding
- Hempel 2-component paint system (or similar):
Primer HEMPADUR 47200, paint thickness (DFT) 50 - 60 µm with
Top coat HEMPEL HEMPATHANE HS 55610, paint thickness (DFT) 50 - 60 µm
OR
HEMPATHANE FAST DRY 55750, paint thickness (DFT) 100 - 120 µm
- Total paint thickness (DFT) 100 - 120 µm

Warranty:

One year limited warranty, except wear and tear and mishandling.

Specification for Quotation Q_____
Seacom – Gooseneck SH36 XT



Dimensions SH36 XT (approx.):

Overall length:	4,795 mm
Overall height:	1,745 mm
King pin height:	1,280 mm
Rear swing clearance:	1,800 mm
Width ballast weight:	900 mm
Width gooseneck:	340 mm
Length king pin – end of ballast weight:	1,675 mm
King pin diameter:	2"

Dimensions park stand - optional (approx.):

Length x Width x Height:	4,050 x 1,800 x 590 mm
--------------------------	------------------------

Weights (approx.):

Weight of gooseneck	3,250 kg
Weight of park stand (optional):	1,000 kg
Required fifth wheel capacity:	36,000 kg

